

SAFETY DATA SHEET

Issuing Date 07-May-2015

Revision Date 07-May-2018

Revision Number 3

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Corona

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Fuel additive

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name Enertech Labs, Inc.

Supplier Address 714 Northland Ave
Buffalo
NY
14211
US

Supplier Phone Number Phone:800-759-2080
Fax:716-597-0217
Contact Phone716-332-9074

Supplier Email sales@enertechlabs.com

Emergency telephone number Chemtrec 800-424-9300

2. HAZARDS IDENTIFICATION

Classification


This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 4
Acute toxicity - Inhalation (Vapors)	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2

Germ cell mutagenicity	Category 1B
Carcinogenicity	Category 1B
Specific target organ toxicity (repeated exposure)	Category 2
Aspiration toxicity	Category 1
Flammable liquids	Category 4

GHS Label elements, including precautionary statements

Emergency Overview

Signal word	Danger	
Hazard Statements		
Harmful if swallowed		
Harmful in contact with skin		
Harmful if inhaled		
Causes skin irritation		
Causes serious eye irritation		
May cause genetic defects		
May cause cancer		
May cause damage to organs through prolonged or repeated exposure		
May be fatal if swallowed and enters airways		
Combustible liquid		
		
Appearance	Amber	Physical state
		Liquid
		Odor
		Sweet

Precautionary Statements - Prevention

- Obtain special instructions before use
- Do not handle until all safety precautions have been read and understood
- Use personal protective equipment as required
- Wash face, hands and any exposed skin thoroughly after handling
- Do not eat, drink or smoke when using this product
- Use only outdoors or in a well-ventilated area
- Do not breathe dust/fume/gas/mist/vapors/spray
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking
- Wear eye/face protection

Precautionary Statements - Response

- IF exposed or concerned: Get medical advice/attention
- Specific treatment (see .? on this label)
- Specific treatment (see supplemental first aid instructions on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice/attention

Skin

IF ON SKIN: Wash with plenty of soap and water
Call a POISON CENTER or doctor/physician if you feel unwell
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Ingestion

Rinse mouth
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0% of the mixture consists of ingredient(s) of unknown toxicity

Other information

Toxic to aquatic life with long lasting effects
Harmful to aquatic life
PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION
INHALATION MAY CAUSE CENTRAL NERVOUS SYSTEM EFFECTS

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
butyl cellosolve	111-76-2	30 - 60	*
Xylene	1330-20-7	7 - 13	*
Naphtha (petroleum), heavy aromatic	64742-94-5	7 - 13	*
Petroleum naphtha, light aromatic	64742-95-6	5 - 10	*
1,2,4 Trimethylbenzene	95-63-6	5 - 10	*
Ethylene glycol	107-21-1	3 - 7	*
1,3,5-Trimethylbenzene	108-67-8	1 - 5	*
Naphthalene	91-20-3	1 - 5	*
Ethylbenzene	100-41-4	1 - 5	*
Diethyl Benzene	25340-17-4	1 - 5	*
Cumene	98-82-8	1 - 5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

First aid measures

General Advice

Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.

Eye contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. Do not rub affected area.

Skin contact

Wash off immediately with soap and plenty of water for at least 15 minutes. If symptoms persist, call a physician.

Inhalation

Remove to fresh air. Get medical attention immediately if symptoms occur. Aspiration into lungs can produce severe lung damage. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. If breathing is difficult, (trained personnel should) give oxygen. Delayed pulmonary edema may occur.

Ingestion

Rinse mouth immediately and drink plenty of water. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Aspiration hazard if swallowed - can enter lungs and cause damage. If vomiting occurs spontaneously, keep head below hips to prevent aspiration. Call a physician or poison control center immediately.

Self-protection of the first aider

Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Wear personal protective clothing (see section 8). Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Remove all sources of ignition.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects Burning sensation. Coughing and/ or wheezing. Difficulty in breathing. Dizziness.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray.

Uniform Fire Code	Irritant: Liquid Toxic: Liquid Combustible Liquid: III-A
--------------------------	----------------------------------------------------------------

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge Yes.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal protective equipment as required. Avoid breathing vapors or mists. Avoid generation of dust. Evacuate personnel to safe areas. See section 8 for more information. Take precautionary measures against static discharges. Do not touch or walk through spilled material.

Other Information Refer to protective measures listed in Sections 7 and 8.

Environmental precautions

Environmental precautions Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Do not touch or walk through spilled material. Dike far ahead of liquid spill for later disposal.

Methods for cleaning up Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Do not breathe dust/fume/gas/mist/vapors/spray.

Conditions for safe storage, including any incompatibilities

Storage Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Protect from moisture. Store away from other materials. Store locked up. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products Strong acids. Strong oxidizing agents. Strong bases.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH

butyl cellosolve 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m ³ (vacated) S*	IDLH: 700 ppm TWA: 5 ppm TWA: 24 mg/m ³
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	
1,2,4 Trimethylbenzene 95-63-6	-	-	TWA: 25 ppm TWA: 125 mg/m ³
Ethylene glycol 107-21-1	Ceiling: 100 mg/m ³ aerosol only	(vacated) Ceiling: 50 ppm (vacated) Ceiling: 125 mg/m ³	
1,3,5-Trimethylbenzene 108-67-8	-	-	TWA: 25 ppm TWA: 125 mg/m ³
Naphthalene 91-20-3	TWA: 10 ppm S*	TWA: 10 ppm TWA: 50 mg/m ³ (vacated) TWA: 10 ppm (vacated) TWA: 50 mg/m ³ (vacated) STEL: 15 ppm (vacated) STEL: 75 mg/m ³	IDLH: 250 ppm TWA: 10 ppm TWA: 50 mg/m ³ STEL: 15 ppm STEL: 75 mg/m ³
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m ³ (vacated) S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m ³

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters

Appropriate engineering controls

Engineering Measures

Showers
Eyewash stations
Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection

None required for consumer use. If splashes are likely to occur: Tight sealing safety goggles.

Skin and body protection

Wear protective gloves and protective clothing. Long sleeved clothing. Impervious gloves.

Respiratory protection

No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace.

Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical state	Liquid	Odor	Sweet
Appearance	Amber	Odor Threshold	No information available
Color	No information available		

Property	Values	Remarks	Method
pH	UNKNOWN	None known	
Melting / freezing point	No data available	None known	
Boiling point / boiling range	113 °C / 235 °F	None known	
Flash Point	61 C / 142 F	None known	
Evaporation Rate	No data available	None known	
Flammability (solid, gas)	No data available	None known	
Flammability Limit in Air			
Upper flammability limit	No data available		
Lower flammability limit	No data available		
Vapor pressure	No data available	None known	
Vapor density	No data available	None known	
Specific Gravity	No data available	None known	
Water Solubility	Slightly soluble	None known	
Solubility in other solvents	No data available	None known	
Partition coefficient: n-octanol/water	No data available	None known	
Autoignition temperature	No data available	None known	
Decomposition temperature	No data available	None known	
Kinematic viscosity	No data available	None known	
Dynamic viscosity	4.8	None known	
Explosive properties	No data available		
Oxidizing properties	No data available		

Other Information

Softening Point	No data available
VOC Content (%)	No data available
Particle Size	No data available
Particle Size Distribution	

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Excessive heat. Heat, flames and sparks.

Incompatible materials

Strong acids. Strong oxidizing agents. Strong bases.

Hazardous Decomposition Products

Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation

Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Harmful by inhalation. (based on components). Aspiration into lungs can produce severe lung damage. May cause pulmonary edema. Pulmonary edema can be fatal.

Eye contact

Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to eyes. May cause redness, itching, and pain. May cause temporary eye irritation. May cause irritation.

Skin contact

Specific test data for the substance or mixture is not available. Expected to be an irritant based on components. Irritating to skin. Prolonged contact may cause redness and irritation. May be absorbed through the skin in harmful amounts. Harmful in contact with skin. (based on components). Repeated exposure may cause skin dryness or cracking.

Ingestion

Specific test data for the substance or mixture is not available. Ingestion may cause irritation to mucous membranes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Harmful if swallowed. (based on components). Potential for aspiration if swallowed. May cause lung damage if swallowed. Aspiration may cause pulmonary edema and pneumonitis. May be fatal if swallowed and enters airways.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
butyl cellosolve 111-76-2	= 470 mg/kg (Rat)	= 220 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h
Xylene 1330-20-7	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 47635 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Naphtha (petroleum), heavy aromatic 64742-94-5	> 5000 mg/kg (Rat)	> 2 mL/kg (Rabbit)	> 590 mg/m ³ (Rat) 4 h

Petroleum naphtha, light aromatic 64742-95-6	-	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat) 4 h = 3400 ppm (Rat) 4 h
1,2,4-Trimethylbenzene 95-63-6	= 3400 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m ³ (Rat) 4 h
Ethylene glycol 107-21-1	= 4000 mg/kg (Rat)	-	-
1,3,5-Trimethylbenzene 108-67-8	-	-	= 24 g/m ³ (Rat) 4 h
Naphthalene 91-20-3	-	> 20 g/kg (Rabbit)	> 340 mg/m ³ (Rat) 1 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15354 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h
Cumene 98-82-8	= 1400 mg/kg (Rat)	= 12300 µL/kg (Rabbit)	-

Information on toxicological effects

Symptoms Erythema (skin redness). May cause redness and tearing of the eyes. Coughing and/ or wheezing. Difficulty in breathing. Asthma-like and/ or skin allergy-like symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects Contains a known or suspected mutagen.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
butyl cellosolve 111-76-2	A3	Group 3		
Xylene 1330-20-7		Group 3		
Naphthalene 91-20-3	A3	Group 2B	Reasonably Anticipated	X
Ethylbenzene 100-41-4	A3	Group 2B		X
Cumene 98-82-8		Group 2B		X

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

NTP (National Toxicology Program)

Reasonably Anticipated - Reasonably Anticipated to be a Human Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure Causes damage to organs through prolonged or repeated exposure. Based on classification criteria from the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from chronic or repeated exposure. (STOT RE).

Chronic Toxicity Contains a known or suspected mutagen. Possible risk of irreversible effects. Contains a

known or suspected carcinogen. Aspiration may cause pulmonary edema and pneumonitis. Avoid repeated exposure. Prolonged exposure may cause chronic effects. May cause adverse effects on the bone marrow and blood-forming system. May cause adverse liver effects.

Target Organ Effects

Respiratory system. Eyes. Skin. May affect the genetic material in germ cells (sperm and eggs). Gastrointestinal tract (GI). Blood. Central Nervous System (CNS). Hematopoietic system. Kidney. Liver. Heart. Lungs. Nasal cavities. Thyroid. Central Vascular System (CVS). Testes.

Aspiration Hazard

No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral)

825.00 mg/kg

ATEmix (dermal)

1,826.00 mg/kg (ATE)

ATEmix (inhalation-gas)

7,494.00 ppm (4 hr)

ATEmix (inhalation-dust/mist)

2.00 mg/l

ATEmix (inhalation-vapor)

18.00 ATEmix

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life. Toxic to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
butyl cellosolve, 111-78-2		96h LC50: = 1490 mg/L (Lepomis macrochirus) 96h LC50: = 2950 mg/L (Lepomis macrochirus)		48h EC50: > 1000 mg/L 24h EC50: 1698 - 1940 mg/L
Xylene 1330-20-7		96h LC50: = 13.4 mg/L (Pimephales promelas) 96h LC50: 2.861 - 4.093 mg/L (Oncorhynchus mykiss) 96h LC50: 13.5 - 17.3 mg/L (Oncorhynchus mykiss) 96h LC50: 13.1 - 16.5 mg/L (Lepomis macrochirus) 96h LC50: = 19 mg/L (Lepomis macrochirus) 96h LC50: 7.711 - 9.591 mg/L (Lepomis macrochirus) 96h LC50: 23.53 - 29.97 mg/L (Pimephales promelas) 96h LC50: = 780 mg/L (Cyprinus carpio) 96h LC50: > 780 mg/L (Cyprinus carpio) 96h LC50: 30.26 - 40.75 mg/L (Poecilia reticulata)	EC50 = 0.0084 mg/L 24 h	48h EC50: = 3.82 mg/L 48h LC50: = 0.6 mg/L
Naphtha (petroleum), heavy aromatic 64742-94-5	72h EC50: = 2.5 mg/L (Skeletonema costatum)	96h LC50: = 19 mg/L (Pimephales promelas) 96h LC50: = 2.34 mg/L (Oncorhynchus mykiss) 96h LC50: = 1740 mg/L (Lepomis macrochirus) 96h LC50: = 45 mg/L (Pimephales promelas) 96h LC50: = 41 mg/L (Pimephales promelas)		48h EC50: = 0.95 mg/L
Petroleum naphtha, light aromatic 64742-95-8		96h LC50: = 9.22 mg/L (Oncorhynchus mykiss)		48h EC50: = 6.14 mg/L
1,2,4 Trimethylbenzene 95-63-8		96h LC50: 7.19 - 8.28 mg/L (Pimephales promelas)		48h EC50: = 6.14 mg/L
Ethylene glycol 107-21-1	96h EC50: 6500 - 13000 mg/L (Pseudokirchneriella subcapitata)	96h LC50: = 41000 mg/L (Oncorhynchus mykiss) 96h LC50: 14 - 18 mL/L (Oncorhynchus mykiss) 96h LC50: = 40761 mg/L (Oncorhynchus mykiss) 96h LC50: = 27540 mg/L (Lepomis macrochirus) 96h LC50: = 16000 mg/L (Poecilia reticulata) 96h LC50: 40000 - 60000 mg/L (Pimephales promelas)	EC50 = 10000 mg/L 16 h EC50 = 620 mg/L 30 min EC50 = 620.0 mg/L 30 min	48h EC50: = 46300 mg/L
1,3,5-Trimethylbenzene 108-67-8		96h LC50: = 3.48 mg/L (Pimephales promelas)		24h EC50: = 50 mg/L
Naphthalene 91-20-3	72h EC50: = 0.4 mg/L (Skeletonema costatum)	96h LC50: 5.74 - 6.44 mg/L (Pimephales promelas) 96h LC50: = 1.6 mg/L (Oncorhynchus mykiss) 96h LC50: 0.91 - 2.82 mg/L (Oncorhynchus mykiss) 96h LC50: = 1.99 mg/L (Pimephales promelas) 96h LC50: = 31.0265 mg/L (Lepomis macrochirus)	EC50 = 0.93 mg/L 30 min EC50 > 20 mg/L 18 h	48h LC50: = 2.16 mg/L 48h EC50: = 1.96 mg/L 48h EC50: 1.09 - 3.4 mg/L
Ethylbenzene 100-41-4	72h EC50: = 4.6 mg/L (Pseudokirchneriella subcapitata) 96h EC50: > 438 mg/L (Pseudokirchneriella subcapitata) 72h EC50: 2.6 - 11.3 mg/L (Pseudokirchneriella subcapitata) 96h EC50: 1.7 - 7.6 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 11.0 - 18.0 mg/L (Oncorhynchus mykiss) 96h LC50: = 4.2 mg/L (Oncorhynchus mykiss) 96h LC50: 7.55 - 11 mg/L (Pimephales promelas) 96h LC50: = 32 mg/L (Lepomis macrochirus) 96h LC50: 9.1 - 15.6 mg/L (Pimephales promelas) 96h LC50: = 9.6 mg/L (Poecilia reticulata)	EC50 = 9.88 mg/L 30 min EC50 = 96 mg/L 24 h	48h EC50: 1.8 - 2.4 mg/L
Cumene 98-82-8	72h EC50: = 2.6 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 6.04 - 6.61 mg/L (Pimephales promelas) 96h LC50: = 4.8 mg/L (Oncorhynchus mykiss) 96h LC50: = 2.7 mg/L (Oncorhynchus mykiss) 96h LC50: = 5.1 mg/L (Poecilia reticulata)	EC50 = 0.89 mg/L 5 min EC50 = 1.10 mg/L 15 min EC50 = 1.48 mg/L 30 min EC50 = 172 mg/L 24 h	48h EC50: = 0.6 mg/L 48h EC50: 7.9 - 14.1 mg/L

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
2-Butoxyethanol 111-76-2	0.81
Xylene 1330-20-7	3.15
Naphtha (petroleum), heavy aromatic 64742-94-5	6.1
1,2,4 Trimethylbenzene 95-63-8	3.63
Ethylene glycol 107-21-1	-1.93
Naphthalene 91-20-3	3.3
Ethylbenzene 100-41-4	3.118
Cumene 98-82-8	3.55



Other adverse effects
No information available.

Item 739

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated Packaging

Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number

U055 U165 U239

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7		Included in waste stream: F039		U239
Naphthalene 91-20-3	U165	Included in waste streams: F024, F025, F034, F039, K001, K035, K060, K087, K145		U165
Ethylbenzene 100-41-4		Included in waste stream: F039		
Cumene 98-82-8				U055

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Naphthalene 91-20-3			Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Xylene 1330-20-7	Toxic Ignitable
1,2,4 Trimethylbenzene 95-63-6	Toxic
Naphthalene 91-20-3	Toxic
Ethylbenzene 100-41-4	Toxic Ignitable
Cumene 98-82-8	Toxic Ignitable

14. TRANSPORT INFORMATION

<u>DOT</u>	NOT REGULATED
Proper Shipping Name	NON REGULATED
Hazard Class	N/A
<u>TDG</u>	Not regulated
<u>MEX</u>	Not regulated
<u>ICAO</u>	Not regulated
<u>IATA</u>	Not regulated
Proper Shipping Name	NON REGULATED
Hazard Class	N/A
<u>IMDG/IMO</u>	Not regulated
Hazard Class	N/A
Marine Pollutant	Product is a marine pollutant according to the criteria set by IMDG/IMO
<u>RID</u>	Not regulated
<u>ADR</u>	Not regulated
<u>ADN</u>	Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	Complies
DSL	All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
butyl cellosolve - 111-76-2	111-76-2	30 - 60	1.0
Xylene - 1330-20-7	1330-20-7	7 - 13	1.0
1,2,4 Trimethylbenzene - 95-63-6	95-63-6	5 - 10	1.0
Ethylene glycol - 107-21-1	107-21-1	3 - 7	1.0
Naphthalene - 91-20-3	91-20-3	1 - 5	0.1
Ethylbenzene - 100-41-4	100-41-4	1 - 5	0.1
Cumene - 98-82-8	98-82-8	1 - 5	1.0

SARA 311/312 Hazard Categories

Acute Health Hazard	Yes
Chronic Health Hazard	Yes
Fire Hazard	Yes

Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb			X
Naphthalene 91-20-3	100 lb	X	X	X
Ethylbenzene 100-41-4	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Xylene 1330-20-7	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylene glycol 107-21-1	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
Naphthalene 91-20-3	100 lb		RQ 100 lb final RQ RQ 45.4 kg final RQ RQ 0.454 kg final RQ
Ethylbenzene 100-41-4	1000 lb		RQ 1000 lb final RQ RQ 454 kg final RQ
Cumene 98-82-8	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations**California Proposition 65**

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Ethylbenzene - 100-41-4	Carcinogen
Naphthalene - 91-20-3	Carcinogen
Cumene - 98-82-8	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
butyl cellosolve 111-76-2	X	X	X	X	X
Xylene 1330-20-7	X	X	X	X	X
1,2,4 Trimethylbenzene 95-63-6	X	X	X	X	X
Ethylene glycol 107-21-1	X	X	X	X	X
1,3,5-Trimethylbenzene 108-67-8	X	X	X		X
Naphthalene 91-20-3	X	X	X	X	X
Ethylbenzene 100-41-4	X	X	X	X	X
Cumene 98-82-8	X	X	X	X	X

Diethyl Benzene 25340-17-4	X				
-------------------------------	---	--	--	--	--

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
butyl cellosolve 111-76-2 (30 - 60)		Mexico: TWA 26 ppm Mexico: TWA 120 mg/m ³ Mexico: STEL 75 ppm Mexico: STEL 360 mg/m ³
Xylene 1330-20-7 (7 - 13)		Mexico: TWA 100 ppm Mexico: TWA 435 mg/m ³ Mexico: STEL 150 ppm Mexico: STEL 655 mg/m ³
1,2,4 Trimethylbenzene 95-63-6 (5 - 10)		Mexico: TWA 25 ppm Mexico: TWA 125 mg/m ³ Mexico: STEL 35 ppm Mexico: STEL 170 mg/m ³
Ethylene glycol 107-21-1 (3 - 7)		Mexico: Ceiling 100 mg/m ³
1,3,5-Trimethylbenzene 108-67-8 (1 - 5)		Mexico: TWA 25 ppm Mexico: TWA 125 mg/m ³ Mexico: STEL 35 ppm Mexico: STEL 170 mg/m ³
Naphthalene 91-20-3 (1 - 5)		Mexico: TWA 10 ppm Mexico: TWA 50 mg/m ³ Mexico: STEL 15 ppm Mexico: STEL 75 mg/m ³
Ethylbenzene 100-41-4 (1 - 5)		Mexico: TWA 100 ppm Mexico: TWA 435 mg/m ³ Mexico: STEL 125 ppm Mexico: STEL 545 mg/m ³
Cumene 98-82-8 (1 - 5)		Mexico: TWA 50 ppm Mexico: TWA 245 mg/m ³ Mexico: STEL 75 ppm Mexico: STEL 365 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

- B3 - Combustible liquid
- D2A - Very toxic materials
- D2B - Toxic materials



16. OTHER INFORMATION

NFPA	Health Hazards 3	Flammability 2	Instability 0	Physical and Chemical Hazards -
HMIS	Health Hazards 2 *	Flammability 2	Physical Hazard 0	Personal Protection X

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 07-May-2015
Revision Date 07-May-2015
Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet