

Safety Data Sheet

#92

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Issue date: 09/23/2024 Revision date: 09/23/2024 Supersedes: 04/02/2024

Version: 1.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ.
Product code : 4615

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Technical Chemical Company
P.O. BOX 139
Cleburne, Texas 76033
T 817-645-6088

1.4. Emergency telephone number

Emergency number : CHEMTREC 24 Hour 1-800-424-9300, 1-703-527-3887 (International)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS US classification

| | |
|--|---|
| Flammable liquids Category 2 | H225 Highly flammable liquid and vapor |
| Skin corrosion/irritation Category 2 | H315 Causes skin irritation |
| Carcinogenicity Category 1B | H350 May cause cancer |
| Specific target organ toxicity — Single exposure, Category 3, Narcosis | H336 May cause drowsiness or dizziness |
| Aspiration hazard Category 1 | H304 May be fatal if swallowed and enters airways |
| Hazardous to the aquatic environment - Chronic Hazard Category 1 | H410 Very toxic to aquatic life with long lasting effects |

Full text of H- and EUH-statements: see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H350 - May cause cancer
H410 - Very toxic to aquatic life with long lasting effects

Precautionary statements (GHS US) :

P201 - Obtain special instructions
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof electrical, ventilating, lighting equipment
P242 - Use only non-sparking tools.
P243 - Take precautionary measures against static discharge.
P261 - Avoid breathing dust, fume, gas, mist, vapor spray
P264 - Wash affected areas thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection
P301+P310 - If swallowed: Immediately call a poison control center, doctor, physician,
P302+P352 - If on skin: Wash with plenty of soap and water
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P312 - Call a POISON CONTROL CENTER, doctor, if you feel unwell.
P321 - Specific treatment: See section 4.1 on SDS
P331 - Do NOT induce vomiting.
P332+P313 - If skin irritation occurs: Get medical advice/attention.

JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#92

P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: See Section 5.1 Extinguishing Media
P391 - Collect spillage.
P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

| Name | Product identifier | % | GHS US classification |
|---------------------------------------|-----------------------|---------------|---|
| Heptane, Branched Cyclic | (CAS-No.) 426260-76-6 | 30 – 50 | Flam. Liq. 1, H224 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 3, H412 |
| Petrolatum | (CAS-No.) 8009-03-8 | 10 – 30 | Carc. 1B, H350 |
| Petroleum Gases, Liquefied, Sweetened | (CAS-No.) 68476-86-8 | 10 – 30 | Flam. Gas 1, H220 Press. Gas (Comp.), H280 Muta. 1B, H340 Carc. 1A, H350 |
| n-Heptane | (CAS-No.) 142-82-5 | 1 – 5 | Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410 |
| Xylene, Mixture of Isomers | (CAS-No.) 1330-20-7 | 0.032 – 0.064 | Flam. Liq. 3, H226 Skin Irrit. 2, H315 |
| Ethylbenzene | (CAS-No.) 100-41-4 | < 1 | Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304 |
| Dipropylene Glycol Monomethyl Ether | (CAS-No.) 34590-94-8 | < 1 | Flam. Liq. 4, H227 |

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention. Specific treatment: See section 4.1 on SDS.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists.
- First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/effects : May cause cancer.
- Symptoms/effects after inhalation : May cause drowsiness or dizziness.
- Symptoms/effects after skin contact : Causes skin irritation.
- Symptoms/effects after ingestion : May be fatal if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#92

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor.
Explosion hazard : May form flammable/explosive vapor-air mixture.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection. Avoid breathing dust,fume,gas,mist,vapor spray.
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools. Obtain special instructions . Do not handle until all safety precautions have been read and understood. Avoid breathing dust,fume,gas,mist,vapor spray. Use only outdoors or in a well-ventilated area.
Hygiene measures : Wash affected areas thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating, lighting equipment.
Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Keep in fireproof place. Keep container tightly closed.
Incompatible products : Strong bases. Strong acids.
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| | |
|--|---------|
| JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ. | |
| No additional information available | |
| n-Heptane (142-82-5) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA | 400 ppm |
| ACGIH OEL STEL | 500 ppm |
| Heptane, Branched Cyclic (426260-76-6) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA | 400 ppm |
| ACGIH OEL STEL | 500 ppm |

JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#92

| USA - OSHA - Occupational Exposure Limits | |
|--|--|
| OSHA PEL TWA | 500 ppm |
| Petrolatum (8009-03-8) | |
| No additional information available | |
| Xylene, Mixture of Isomers (1330-20-7) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA | 20 ppm |
| Ethylbenzene (100-41-4) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA | 20 ppm |
| Dipropylene Glycol Monomethyl Ether (34590-94-8) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA | 50 ppm |
| Petroleum Gases, Liquefied, Sweetened (68476-86-8) | |
| USA - ACGIH - Occupational Exposure Limits | |
| ACGIH OEL TWA | 1000 ppm Listed under Aliphatic hydrocarbon gases alkane C1-C4 |
| USA - OSHA - Occupational Exposure Limits | |
| OSHA PEL TWA | 1800 mg/m ³ 1000 ppm |
| USA - NIOSH - Occupational Exposure Limits | |
| NIOSH REL (TWA) | 1800 mg/m ³ 1000 ppm |

8.2. Appropriate engineering controls

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Protective goggles. Wear protective clothing. Avoid all unnecessary exposure.

Hand protection:

Wear protective gloves

Eye protection:

Chemical goggles or safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Where exposure through inhalation may occur from use, respiratory protection equipment is recommended. Wear respiratory protection.

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|---------------------|
| Physical state | : Gas |
| Color | : Colorless. |
| Odor | : characteristic. |
| Odor threshold | : No data available |
| pH | : No data available |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Melting point | : No data available |

JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#92

| | |
|---|---------------------|
| Freezing point | : No data available |
| Boiling point | : No data available |
| Flash point | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Flammability | : No data available |
| Vapor pressure | : No data available |
| Relative vapor density at 20 °C | : No data available |
| Relative density | : No data available |
| Solubility | : No data available |
| Partition coefficient n-octanol/water (Log Pow) | : No data available |
| Partition coefficient n-octanol/water (Log Kow) | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |
| Explosion limits | : No data available |

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Toxic fume. . Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

| | |
|-----------------------------|------------------|
| Acute toxicity (oral) | : Not classified |
| Acute toxicity (dermal) | : Not classified |
| Acute toxicity (inhalation) | : Not classified |

| n-Heptane (142-82-5) | |
|---|---|
| LD50 oral rat | > 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Read-across, Oral, 14 day(s)) |
| LD50 dermal rabbit | > 2000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Dermal, 14 day(s)) |
| LC50 Inhalation - Rat | > 29.29 mg/l/4h (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours)) |
| Heptane, Branched Cyclic (426260-76-6) | |
| LD50 oral rat | > 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Read-across, Oral, 14 day(s)) |
| LD50 dermal rabbit | > 2000 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male / female, Read-across, Dermal, 14 day(s)) |
| LC50 Inhalation - Rat | > 29.29 mg/l/4h (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours)) |
| Xylene, Mixture of Isomers (1330-20-7) | |
| LD50 oral rat | > 4000 mg/kg body weight (Equivalent or similar to EU Method B.1, Rat, Female, Experimental value, Oral, 14 day(s)) |
| LD50 dermal rabbit | > 4200 mg/kg (Rabbit; Experimental value,Rabbit; Experimental value) |

JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#92

| Xylene, Mixture of Isomers (1330-20-7) | |
|---|--|
| LC50 Inhalation - Rat | 29.09 mg/l (Equivalent or similar to EU Method B.2, 4 h, Rat, Male, Experimental value, Inhalation (vapours), 14 day(s)) |
| ATE US (vapors) | 29.09 mg/l/4h |
| ATE US (dust, mist) | 29.09 mg/l/4h |

| Ethylbenzene (100-41-4) | |
|--------------------------------|---|
| LD50 oral rat | 3500 mg/kg (Rat, Male / female, Experimental value, Oral, 14 day(s)) |
| LD50 dermal rabbit | 15433 mg/kg body weight (24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s)) |
| LC50 Inhalation - Rat | 17.8 mg/l (4 h, Rat, Male, Experimental value, Inhalation (vapours), 14 day(s)) |
| ATE US (oral) | 3500 mg/kg body weight |
| ATE US (dermal) | 15433 mg/kg body weight |
| ATE US (gases) | 4500 ppmV/4h |
| ATE US (vapors) | 17.8 mg/l/4h |
| ATE US (dust, mist) | 1.5 mg/l/4h |

| Dipropylene Glycol Monomethyl Ether (34590-94-8) | |
|---|---|
| LD50 oral rat | > 5000 mg/kg (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 14 day(s)) |
| LD50 dermal rabbit | 9510 mg/kg body weight (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal, 14 day(s)) |
| ATE US (dermal) | 9510 mg/kg body weight |

Skin corrosion/irritation : Causes skin irritation.
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : May cause cancer.

| Xylene, Mixture of Isomers (1330-20-7) | |
|---|----------------------|
| IARC group | 3 - Not classifiable |

Reproductive toxicity : Not classified
STOT-single exposure : May cause drowsiness or dizziness.

| n-Heptane (142-82-5) | |
|-----------------------------|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |

| Heptane, Branched Cyclic (426260-76-6) | |
|---|------------------------------------|
| STOT-single exposure | May cause drowsiness or dizziness. |

STOT-repeated exposure : Not classified

| Ethylbenzene (100-41-4) | |
|--------------------------------|--|
| STOT-repeated exposure | May cause damage to organs through prolonged or repeated exposure. |

Aspiration hazard : May be fatal if swallowed and enters airways.
Viscosity, kinematic : No data available
Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.
Symptoms/effects : May cause cancer.
Symptoms/effects after inhalation : May cause drowsiness or dizziness.
Symptoms/effects after skin contact : Causes skin irritation.
Symptoms/effects after ingestion : May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - water : Hazardous to aquatic environment chronic toxicity-Catogory 1
Very toxic to aquatic life with long lasting effects.
Ecology - water : Very toxic to aquatic life with long lasting effects.

| Xylene, Mixture of Isomers (1330-20-7) | |
|---|---|
| LC50 - Fish [1] | 2.6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static renewal, Fresh water, Read-across, Lethal) |
| ErC50 algae | 4.4 mg/l (OECD 201: Alga, Growth Inhibition Test, 73 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP) |

JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#92

| Ethylbenzene (100-41-4) | |
|---|---|
| LC50 - Fish [1] | 5.1 mg/l (ASTM, 96 h, Menidia menidia, Flow-through system, Salt water, Experimental value, Lethal) |
| EC50 - Crustacea [1] | 1.8 – 2.4 mg/l (US EPA, 48 h, Daphnia magna, Static system, Fresh water, Experimental value) |
| Dipropylene Glycol Monomethyl Ether (34590-94-8) | |
| LC50 - Fish [1] | > 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Poecilia reticulata, Static system, Fresh water, Experimental value, GLP) |
| ErC50 algae | > 969 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP) |

12.2. Persistence and degradability

| JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ. | |
|---|--|
| Persistence and degradability | Biodegradability in soil: no data available. Biodegradable in the soil under anaerobic conditions. Not established. |
| n-Heptane (142-82-5) | |
| Persistence and degradability | Readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Low potential for adsorption in soil. Photolysis in the air. Not established. |
| Biochemical oxygen demand (BOD) | 1.92 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 0.06 g O ₂ /g substance |
| ThOD | 3.52 g O ₂ /g substance |
| Heptane, Branched Cyclic (426260-76-6) | |
| Persistence and degradability | May cause long-term adverse effects in the environment. |
| Petrolatum (8009-03-8) | |
| Persistence and degradability | Not established. |
| Xylene, Mixture of Isomers (1330-20-7) | |
| Persistence and degradability | Biodegradable in the soil. Readily biodegradable in water. |
| Ethylbenzene (100-41-4) | |
| Persistence and degradability | Biodegradable in the soil. Readily biodegradable in water. Not established. |
| Biochemical oxygen demand (BOD) | 1.44 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 2.1 g O ₂ /g substance |
| ThOD | 3.17 g O ₂ /g substance |
| Dipropylene Glycol Monomethyl Ether (34590-94-8) | |
| Persistence and degradability | Readily biodegradable in water. |
| Biochemical oxygen demand (BOD) | 0 g O ₂ /g substance |
| ThOD | 2.06 g O ₂ /g substance |
| Petroleum Gases, Liquefied, Sweetened (68476-86-8) | |
| Persistence and degradability | Not established. |

12.3. Bioaccumulative potential

| JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ. | |
|--|--|
| Bioaccumulative potential | Not established. |
| n-Heptane (142-82-5) | |
| BCF - Other aquatic organisms [1] | 552 (BCFBAF v3.00, Calculated value) |
| Partition coefficient n-octanol/water (Log Pow) | 4.5 (Literature) |
| Bioaccumulative potential | Potential for bioaccumulation (4 ≥ Log Kow ≤ 5). Not established. |
| Heptane, Branched Cyclic (426260-76-6) | |
| Bioaccumulative potential | Not established. |
| Petrolatum (8009-03-8) | |
| Bioaccumulative potential | Not established. |
| Xylene, Mixture of Isomers (1330-20-7) | |
| BCF - Fish [1] | 7.2 – 26 (56 day(s), Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across) |
| Partition coefficient n-octanol/water (Log Pow) | 3.2 (Read-across, 20 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). |
| Ethylbenzene (100-41-4) | |
| BCF - Fish [1] | 1 (6 week(s), Oncorhynchus kisutch, Flow-through system, Salt water, Experimental value) |
| Partition coefficient n-octanol/water (Log Pow) | 3.6 (Experimental value, EU Method A.8: Partition Coefficient, 20 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (BCF < 500). Not established. |

JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

#92

| Dipropylene Glycol Monomethyl Ether (34590-94-8) | |
|---|--|
| Partition coefficient n-octanol/water (Log Pow) | 0.004 (Experimental value, OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method, 25 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |
| Petroleum Gases, Liquefied, Sweetened (68476-86-8) | |
| Bioaccumulative potential | Not established. |

12.4. Mobility in soil

| n-Heptane (142-82-5) | |
|--|---|
| Surface tension | 19.66 mN/m (25 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 2.38 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Ecology - soil | Low potential for adsorption in soil. |
| Xylene, Mixture of Isomers (1330-20-7) | |
| Surface tension | 28.01 – 29.76 mN/m (25 °C) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 2.7 (log Koc, Equivalent or similar to OECD 121, Read-across) |
| Ecology - soil | Low potential for adsorption in soil. May be harmful to plant growth, blooming and fruit formation. |
| Ethylbenzene (100-41-4) | |
| Surface tension | 71.2 mN/m (23 °C, 0.058 g/l, EU Method A.5: Surface tension) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 2.71 (log Koc, PCKOCWIN v1.66, QSAR) |
| Ecology - soil | Low potential for adsorption in soil. Toxic to soil organisms. |
| Dipropylene Glycol Monomethyl Ether (34590-94-8) | |
| Surface tension | 68.7 mN/m (20 °C, 1 g/l, OECD 115: Surface Tension of Aqueous Solutions) |
| Organic Carbon Normalized Adsorption Coefficient (Log Koc) | 1 (log Koc, SRC PCKOCWIN v2.0, Calculated value) |
| Ecology - soil | Highly mobile in soil. Not toxic to plants. |

12.5. Other adverse effects

- Effect on global warming : No known effects from this product.
- Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods


- Product/Packaging disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to appropriate waste disposal facility, in accordance with local, regional, national, international regulations.
- Additional information : Handle empty containers with care because residual vapors are flammable.
- Ecological information : Avoid release to the environment. Hazardous waste due to toxicity.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

- Transport document description (DOT) : UN1950 Aerosols (Flammable, (each not exceeding 1 L capacity)), 2.1, Limited Quantity
- UN-No.(DOT) : UN1950
- Proper Shipping Name (DOT) : Aerosols
Flammable, (each not exceeding 1 L capacity)
- Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
- Hazard labels (DOT) : LTD QTY - Limited quantity



- Dangerous for the environment : Yes

JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations


Marine pollutant : Yes



Other information : No supplementary information available.

Transport by sea

UN-No. (IMDG) : UN1950
 Proper Shipping Name (IMDG) : Aerosols (Marine pollutant - heptane)
 Class (IMDG) : 2.1 - Flammable gases
 Hazard labels (IMDG) : LTD QTY - Limited Quantity



Marine pollutant : Yes



Air transport

UN-No. (IATA) : UN1950
 Proper Shipping Name (IATA) : Aerosols
 Class (IATA) : 2.1 - Gases : Flammable
 Hazard labels (IATA) : LTD QTY - Limited Quantity



SECTION 15: Regulatory information

15.1. US Federal regulations

| | |
|--|---|
| JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ. | |
| Subject to reporting requirements of United States SARA Section 313 | |
| SARA Section 311/312 Hazard Classes | Immediate (acute) health hazard Delayed (chronic) health hazard Fire hazard |
| n-Heptane (142-82-5) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| Heptane, Branched Cyclic (426260-76-6) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |
| SARA Section 311/312 Hazard Classes | Fire hazard Immediate (acute) health hazard Delayed (chronic) health hazard |
| Xylene, Mixture of Isomers (1330-20-7) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313 | |
| CERCLA RQ | 100 lb |
| SARA Section 311/312 Hazard Classes | Fire hazard |
| SARA Section 313 - Emission Reporting | 1 % |
| Dipropylene Glycol Monomethyl Ether (34590-94-8) | |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory | |

JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ.**Safety Data Sheet**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Petroleum Gases, Liquefied, Sweetened (68476-86-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SARA Section 311/312 Hazard Classes

Immediate (acute) health hazard
 Fire hazard
 Sudden release of pressure hazard

15.2. International regulations**CANADA****JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ.**

Listed on the Canadian DSL (Domestic Substances List)

n-Heptane (142-82-5)

Listed on the Canadian DSL (Domestic Substances List)

Heptane, Branched Cyclic (426260-76-6)

Listed on the Canadian DSL (Domestic Substances List)

WHMIS Classification

Class B Division 2 - Flammable Liquid
 Class D Division 2 Subdivision B - Toxic material causing other toxic effects

Xylene, Mixture of Isomers (1330-20-7)

Listed on the Canadian DSL (Domestic Substances List)

Dipropylene Glycol Monomethyl Ether (34590-94-8)

Listed on the Canadian DSL (Domestic Substances List)

Petroleum Gases, Liquefied, Sweetened (68476-86-8)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations**Heptane, Branched Cyclic (426260-76-6)****Xylene, Mixture of Isomers (1330-20-7)****Dipropylene Glycol Monomethyl Ether (34590-94-8)****Petroleum Gases, Liquefied, Sweetened (68476-86-8)****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Not classified

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]**15.2.2. National regulations****JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ.**

All components are either listed on the US TSCA Inventory, or are not regulated under TSCA under 40 CFR 720.30.

Heptane, Branched Cyclic (426260-76-6)**Xylene, Mixture of Isomers (1330-20-7)**

Listed on EPA Hazardous Air Pollutant (HAPS)

Dipropylene Glycol Monomethyl Ether (34590-94-8)**Petroleum Gases, Liquefied, Sweetened (68476-86-8)****15.3. US State regulations****JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ.()**

U.S. - California - Proposition 65 - Carcinogens List

No

U.S. - California - Proposition 65 - Developmental Toxicity

Yes

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

Yes

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

No

State or local regulations

U.S. - California - Proposition 65

n-Heptane (142-82-5)

U.S. - California - Proposition 65 - Carcinogens List

U.S. - California - Proposition 65 - Developmental Toxicity

U.S. - California - Proposition 65 - Reproductive Toxicity - Female

U.S. - California - Proposition 65 - Reproductive Toxicity - Male

No significant risk level (NSRL)

No

No

No

No

JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ.**Safety Data Sheet**

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Heptane, Branched Cyclic (426260-76-6) | | | | |
|---|---|---|---|----------------------------------|
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No | No | No | No | |
| Petrolatum (8009-03-8) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No | No | No | No | |
| Xylene, Mixture of Isomers (1330-20-7) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No | No | No | No | |
| Ethylbenzene (100-41-4) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| Yes | No | No | No | |
| Dipropylene Glycol Monomethyl Ether (34590-94-8) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No | No | No | No | |
| Petroleum Gases, Liquefied, Sweetened (68476-86-8) | | | | |
| U.S. - California - Proposition 65 - Carcinogens List | U.S. - California - Proposition 65 - Developmental Toxicity | U.S. - California - Proposition 65 - Reproductive Toxicity - Female | U.S. - California - Proposition 65 - Reproductive Toxicity - Male | No significant risk level (NSRL) |
| No | No | No | No | |
| n-Heptane (142-82-5) | | | | |
| State or local regulations | | | | |
| U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New York City - Right to Know Hazardous Substances List U.S. - Pennsylvania - RTK (Right to Know) List | | | | |
| Xylene, Mixture of Isomers (1330-20-7) | | | | |
| State or local regulations | | | | |
| U.S. - Delaware - Pollutant Discharge Requirements - Reportable Quantities U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - New York City - Right to Know Hazardous Substances List U.S. - Pennsylvania - RTK (Right to Know) List | | | | |
| Ethylbenzene (100-41-4) | | | | |
| State or local regulations | | | | |
| U.S. - California - Proposition 65 | | | | |
| Dipropylene Glycol Monomethyl Ether (34590-94-8) | | | | |
| State or local regulations | | | | |
| U.S. - Idaho - Non-Carcinogenic Toxic Air Pollutants - Acceptable Ambient Concentrations U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List | | | | |

JOHNSEN'S BATTERY TERMINAL PROTECTOR 10 OZ.

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Dipropylene Glycol Monomethyl Ether (34590-94-8)

U.S. – New York City – Right to Know Hazardous Substances List
 U.S. - Pennsylvania - RTK (Right to Know) List


SECTION 16: Other information

Other information : None.

Full text of hazard classes and H-statements:

| | |
|------|---|
| H220 | Extremely flammable gas |
| H224 | Extremely flammable liquid and vapor |
| H225 | Highly flammable liquid and vapor |
| H226 | Flammable liquid and vapor |
| H227 | Combustible liquid |
| H280 | Contains gas under pressure; may explode if heated |
| H304 | May be fatal if swallowed and enters airways |
| H315 | Causes skin irritation |
| H332 | Harmful if inhaled |
| H336 | May cause drowsiness or dizziness |
| H340 | May cause genetic defects |
| H350 | May cause cancer |
| H373 | May cause damage to organs through prolonged or repeated exposure |
| H400 | Very toxic to aquatic life |
| H410 | Very toxic to aquatic life with long lasting effects |
| H412 | Harmful to aquatic life with long lasting effects |

- NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.
- NFPA fire hazard : 3 - Liquids and solids (including finely divided suspended solids) that can be ignited under almost all ambient temperature conditions.
- NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating

- Health : 1 Slight Hazard - Irritation or minor reversible injury possible
- Flammability : 3 Serious Hazard
- Physical : 0 Minimal Hazard
- Personal protection : B

The Supplier identified in Section 1 of this SDS has evaluated this product and certifies it to be labeled and packaged in compliance with the applicable provisions of the Federal Hazardous Substance Act as stated in 16 CFR 1500 and enforced by the Consumer Product Safety Commission, and where applicable the products that require Child Resistant Closures are packaged in accordance with the Poison Prevention Packaging Act as stated in 16 CFR 1700 and enforced by the Consumer Product Safety Commission. All closures have been tested in accordance with the latest protocols. No other testing is required to certify compliance with the above. The date of manufacture is stamped on the product

Disclaimer: The information and recommendations contained herein are based upon tests believed to be reliable. However, the manufacturer/distributor of this product does not guarantee their accuracy or completeness NOR SHALL ANY OF THIS INFORMATION CONSTITUTE A WARRANTY, WHETHER EXPRESSED OR IMPLIED, AS TO THE SAFETY OF THE GOODS, THE MERCHANTABILITY OF THE GOODS, OR THE FITNESS OF THE GOODS FOR A PARTICULAR PURPOSE. Adjustment to conform to actual conditions of usage may be required. The manufacturer/distributor assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits, arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied. Published by Jared Olson