



NORSEMAN
DRILL & TOOL

America's Finest High Speed Steel Cutting Tools™



Type TD²X

Jobber Length 3-Flats on Shank

135° Split Point, Duplex Coating



- Duplex Coating gives **superior wear resistance**.
- **Extreme tool life** vs other drills. **Enhanced surface hardness**.
- Duplex PVD coatings **resist degradation & thermal breakdown** allowing the tool to stay sharp and continue cutting long after normal drills have worn out.
- **Multiple layers create a super smooth finish** that **reduces the possibility of Galling** & gives **extreme tool life** in aluminum applications.



#4010

Type TD²X Drill

Description

Part #	Size	Part #	Size
50502	1/16"	50672	21/64"
50512	5/64"	50682	11/32"
50522	3/32"	50692	23/64"
50532	7/64"	50702	3/8"
50542	1/8"	50712	25/64"
50552	9/64"	50722	13/32"
50562	5/32"	50732	27/64"
50572	11/64"	50742	7/16"
50582	3/16"	50752	29/64"
50592	13/64"	50762	15/32"
50602	7/32"	50772	31/64"
50612	15/64"	50782	1/2"
50622	1/4"		
50632	17/64"		
50642	9/32"		
50652	19/64"		
50662	5/16"		

Part #	Type
50802	BLN-15
50812	BLN-21
50832	BLN-29
50842	BLN-29P

Proudly Manufactured in the USA
with globally sourced material